

TECHNICAL DATA	SIMPLICITA BAG SMART 220 EM	SIMPLICITA BAG SMART 400H	SIMPLICITA BAG SMART 600H
Film	Layflat tubing		
Film thickness* (depending by the film type, size and under approval by Ravizza Packaging technical dept.)	50/250µm - 1.9685/9.84252 mil		
Reel width* (depending by the film type, size and under approval by Ravizza Packaging technical dept.)	40/400 mm - 1.57/15.7"		
Bag lenght	min. 30 mm / max. infinite – min 1.18" / max infinite		
Max. reel diameter	300 mm – 11,81"		
Max. reel weight	18 Kg - 40lb		
Rated supply voltage	110/220 VAC - 50/60 Hz		
Power supply (without accessories)	0.75 kW		
Operating Pressure Range (clean dry air)	4/8 bar - 58/116 psi		
Air consumption (without accessories)	1,5 L / cycle at 6 bar – 0,053 ft ³ /Cycle at 87 psi		
Communication interfaces	-		
Remote assistance	Not available yet		
Machine sizes	555 x 930 x h.430 mm / 21.85 x 36.61 x h.16.92"		
*Depending by the film type, size and under approval by Ravizza Packaging technical department			

Note: Indicated technical data are not binding and may be modified without notice