

TECHNICAL DATA	SIMPLICITA BAG SMART 220 EM	SIMPLICITA BAG SMART 400H	SIMPLICITA BAG SMART 600H
Film	Layflat tubing		
Film thickness* (depending by the film type, size and under approval by Ravizza Packaging technical dept.)	40/100µm – 1,5748/3,93701 mil		
Reel width* (depending by the film type, size and under approval by Ravizza Packaging technical dept.)	80/220 mm – 3,15/8,66"	80/400 mm - 3,15 / 15,7 "	80/600 mm - 3,15 / 23,6 "
Speed in bag per minute (depending by the film type, size, products, system configuration, and under approval by Ravizza Packaging technical dept.)	60 bpm	40 bpm	30 bpm
Bag lenght	min. 50 mm / max. infinite - min. 2" / max. infinite		
Max. reel diameter	300 mm – 11,81"		
Max. reel weight	18 Kg - 40lb		
Rated supply voltage	110/220 VAC - 50/60 Hz		
Power supply (without accessories)	1 kW		
Operating Pressure Range (clean dry air)	4/8 bar - 58/116 psi		
Air consumption (without accessories)	1,5 L / cycle at 6 bar – 0,053 ft ³ /Cycle at 87 psi		
Communication interfaces	Standard: Modbus TCP/IP; Optional: Serial Modbus and predisposition for gateway installation for conversion to other communication protocols		
Remote assistance	Available with access to the customer's local web network		
Machine sizes	640 x 1000 x h. 1170 mm / 25.19 x 39.37 x h. 46,06"	555 x 930 x h.430 mm / 21.85 x 36.61 x h. 16.92"	1020 x 1160 x h.1170 mm / 40.15 x 45.66 x h. 46,06"
*Depending by the the film type, size and under approval by Ravizza Packaging technical department			

Note: Indicated technical data are not binding and may be modified without notice